



SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

SDS # : 083318

CARTER EP 460

Date of the previous version: 2015-04-16

Revision Date: 2015-05-12

Version 2

1. IDENTIFICATION

Product identifier

Product name CARTER EP 460

Other means of identification

Product Code(s) 083318

Number 192
Substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Identified uses Industrial gear oil.

Uses advised against Do not use for any purpose other than the one for which it is intended

Details of the supplier of the safety data sheet

Supplier Address TOTAL Specialties USA Inc
1201 Louisiana Street, Suite 1800
Houston, TX 77002
Phone: +1 800 323 3198

Contact Point Technical/ HSEQ

E-mail Address USRMLIN-info@total.com

Emergency telephone number

Company Phone Number

+1 (908) 862-9300

Emergency telephone

CHEMTREC: +1 800 424 9300 (24h)

2. HAZARDS IDENTIFICATION

Classification

Skin sensitization - Category 1

Label elements



SDS # : 083318

CARTER EP 460

Date of the previous version: 2015-04-16

Revision Date: 2015-05-12

Version 2

**WARNING**

May cause an allergic skin reaction

Precautionary Statements - Prevention

Avoid breathing dust/fume/gas/mist/vapours/ spray
 Contaminated work clothing should not be allowed out of the workplace
 Wear protective gloves

Precautionary Statements - Response

Specific treatment (see Section 4 on this label)

Skin

IF ON SKIN: Wash with plenty of soap and water
 If skin irritation or rash occurs: Get medical advice/attention
 Wash contaminated clothing before reuse

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Unknown Acute Toxicity

No information available

Hazards not otherwise classified (HNOC)

- None known

Other information

- Contaminated surfaces will be extremely slippery
- Should not be released into the environment

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Long chain alkylamine	^	0-5

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES



SDS # : 083318

CARTER EP 460

Date of the previous version: 2015-04-16

Revision Date: 2015-05-12

Version 2

First aid measures for different exposure routes

General advice	IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.
Eye contact	Rinse immediately with plenty of water and seek medical advice.
Skin contact	Remove contaminated clothing and shoes. Wash off with soap and water. Wash contaminated clothing before reuse. Seek medical attention if skin irritation, swelling or redness develops and persists.
Inhalation	Inhalation of high concentrations of vapor or aerosols may cause irritation of the upper respiratory tract.
Ingestion	If swallowed, do not induce vomiting - seek medical advice.

Most important symptoms/effects, acute and delayed

Skin contact	May cause an allergic skin reaction. Avoid contact with skin.
Eye contact	Not classified. May cause eye irritation with susceptible persons.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Symptoms	Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	May cause sensitization of susceptible persons.
---------------------------	---

5. FIRE-FIGHTING MEASURES

<u>Suitable Extinguishing Media</u>	Foam. Carbon dioxide (CO ₂). ABC powder. Water spray.
<u>Unsuitable Extinguishing Media</u>	Do not use a solid water stream as it may scatter and spread fire.
<u>Special Hazard</u>	Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.
<u>Explosion Data</u>	
Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	None.
<u>Protective Equipment and Precautions for Firefighters</u>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.



SDS # : 083318

CARTER EP 460

Date of the previous version: 2015-04-16

Revision Date: 2015-05-12

Version 2

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Evacuate personnel to safe areas. Use personal protective equipment. Remove all sources of ignition.

Other information See Section 12 for additional information.

Environmental precautions

General Information Do not allow material to contaminate ground water system. Local authorities should be advised if significant spillages cannot be contained. Try to prevent the material from entering drains or water courses. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for cleaning up Dam up. Keep in suitable, closed containers for disposal. Soak up with inert absorbent material. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Use mechanical means such as pumps, skimmers and absorbent materials.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.

Hygiene measures Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Use personal protective equipment as required. Wash hands before breaks and at the end of workday. Avoid breathing vapors, mist or gas. Do not use abrasives, solvents or fuels. Do not put product contaminated rags into workwear pockets. Regular cleaning of equipment, work area and clothing is recommended. Avoid prolonged and repeated contact with the skin, especially with used or waste product.

Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions Keep away from food, drink and animal feedingstuffs. Keep in a banded area. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Protect from frost, heat and sunlight. Protect from moisture. Keep in properly labeled containers.

Materials to Avoid Strong oxidizing agents. Reducing agents.



SDS # : 083318

CARTER EP 460

Date of the previous version: 2015-04-16

Revision Date: 2015-05-12

Version 2

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Control parameters****Exposure limits**

Mineral oil mist:

USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined).**Exposure controls****Engineering Measures**

Apply technical measures to comply with the occupational exposure limits. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Individual protection measures, such as personal protective equipment**General Information**

If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.

Eye/Face Protection

If splashes are likely to occur, wear: Safety glasses with side-shields.

Skin and body protection

Protective shoes or boots. Wear suitable protective clothing. Long sleeved clothing.

Hand Protection

Hydrocarbon-proof gloves. Nitrile rubber. Fluorinated rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene measures

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Use personal protective equipment as required. Wash hands before breaks and at the end of workday. Avoid breathing vapors, mist or gas. Do not use abrasives, solvents or fuels. Do not put product contaminated rags into workwear pockets. Regular cleaning of equipment, work area and clothing is recommended. Avoid prolonged and repeated contact with the skin, especially with used or waste product.

9. PHYSICAL AND CHEMICAL PROPERTIES



SDS # : 083318

CARTER EP 460

Date of the previous version: 2015-04-16

Revision Date: 2015-05-12

Version 2

Physical and chemical properties

Color dark amber
 Physical State @20°C liquid
 Odor Oily
 Odor Threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks</u>	<u>Method</u>
pH		Not applicable	
Melting point/range		No information available	
Boiling point/boiling range		Not applicable	
Flash point	277 °C 531 °F		Cleveland Open Cup (COC) ASTM D 92 Cleveland Open Cup (COC). ASTM D 92.
Evaporation rate		No information available	
Flammability Limits in Air		No information available	
upper	-	No information available	
Lower	-	No information available	
Vapor Pressure		No information available	
Vapor density		No information available	
Density	902 kg/m ³	@ 15 °C	ASTM D 1298
Water solubility		Not applicable	
Solubility in other solvents		No information available	
logPow		No information available	
Autoignition temperature		Not applicable	
Decomposition temperature		No information available	
Viscosity, kinematic	460 mm ² /s	@ 40 °C	ASTM D 445
Explosive properties	Not explosive		
Oxidizing Properties	Not applicable		
Possibility of hazardous reactions	Not applicable		
<u>Other information</u>			
Specific Gravity	0.902		ASTM D 1298
Freezing Point		No information available	
Pour point	-15 °C		ASTM D 97
Fire point	293 °C		ASTM D 92

10. STABILITY AND REACTIVITY

<u>Reactivity</u>	No information available.
<u>Chemical stability</u>	Stable under recommended storage conditions.
<u>Possibility of hazardous reactions</u>	None under normal processing.
<u>Conditions to Avoid</u>	Heat, flames and sparks. Take precautionary measures against static discharges. Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Strong oxidizing agents.



SDS # : 083318

CARTER EP 460

Date of the previous version: 2015-04-16

Revision Date: 2015-05-12

Version 2

Incompatible Materials Strong oxidizing agents. Reducing agents.

Hazardous Decomposition Products Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.

11. TOXICOLOGICAL INFORMATION**Acute toxicity****Information on likely routes of exposure****Product Information**

Skin contact	May cause an allergic skin reaction. Avoid contact with skin.
Eye contact	Not classified. May cause eye irritation with susceptible persons.
Inhalation	Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system.
Ingestion	Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Numerical measures of toxicity - Product Information

ATEmix (oral)	5109 mg/kg
ATEmix (dermal)	5109 mg/kg
Inhalation	
ATEmix (inhalation-dust/mist)	5.2 mg/l
ATEmix (inhalation-vapor)	20.5 mg/l

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Long chain alkylamine ^	LD50 612 mg/kg (Rat)	LD50 251 mg/kg (Rabbit)	LC50 (4h) 157 ppm (Rat - gas)

Information on toxicological effects

Symptoms Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause an allergic skin reaction.
Carcinogenicity This product is not classified carcinogenic.

Mutagenicity This product is not classified as mutagenic.
Reproductive toxicity This product does not present any known or suspected reproductive hazards.



SDS # : 083318

CARTER EP 460

Date of the previous version: 2015-04-16

Revision Date: 2015-05-12

Version 2

Other adverse effects Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).

Aspiration Hazard Not classified.

12. ECOLOGICAL INFORMATION**Ecotoxicity****Acute aquatic toxicity - Product Information**

No experimental data available

Acute aquatic toxicity - Component Information

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates	Toxicity to microorganisms
Long chain alkylamine ^	EC50 (72h) 0.44 mg/l (Algae)	LC50 (96h) 1.3 mg/l (Fish)	EC50 (48h) 2.5 mg/l (Daphnia magna)	

Chronic aquatic toxicity - Product Information

No experimental data available

Chronic aquatic toxicity - Component Information

No information available

Effects on terrestrial organisms No experimental data available .**Persistence and degradability****General Information** No information available.**Bioaccumulative potential****Product Information** No information available.**logPow** No information available**Component Information**

Chemical Name	log Pow
Long chain alkylamine ^	2.9

Mobility**Soil** Given its physical and chemical characteristics, the product generally shows low soil mobility



SDS # : 083318

CARTER EP 460

Date of the previous version: 2015-04-16

Revision Date: 2015-05-12

Version 2

Air Loss by evaporation is limited
Water The product is insoluble and floats on water
Other adverse effects

General Information No information available

13. DISPOSAL CONSIDERATIONS**Waste treatment**

Waste Disposal Methods Dispose of in accordance with local regulations.

Contaminated packaging Dispose of in accordance with local regulations.

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

MEX Not regulated

ICAO/IATA Not regulated

IMDG/IMO Not regulated

ADR/RID Not regulated

ADN Not regulated

15. REGULATORY INFORMATION

International Inventories All the substances contained in this product are listed or exempted from listing in the following inventories:
U.S.A. (TSCA)

U.S. Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	no
Fire Hazard	no
Sudden Release of Pressure Hazard	no
Reactive Hazard	no



SDS # : 083318

CARTER EP 460

Date of the previous version: 2015-04-16

Revision Date: 2015-05-12

Version 2

Clean Water Act

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

U.S. State Regulations**California Proposition 65**

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

Chemical Name	Massachusetts	New Jersey	Pennsylvania	Illinois	Rhode Island
Paraffin oils (petroleum), catalytic dewaxed heavy 64742-70-7	X				

16. OTHER INFORMATION

NFPA	Health Hazard 1	Flammability 1	Instability 0	Physical and chemical hazards -
HMIS	Health Hazard 1	Flammability 1	Physical Hazard 0	Personal protection X

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

Revision Date: 2015-05-12
Revision Note No information available
Abbreviations, acronyms



SDS # : 083318

CARTER EP 460

Date of the previous version: 2015-04-16

Revision Date: 2015-05-12

Version 2

Legend

Section 8

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH - National Institute for Occupational Safety and Health

TLV - Threshold Limit Values

PEL - Permissible Exposure Limits

IDHL - Immediately Dangerous to Life or Health concentrations

TWA - Time Weight Average

STEL - Short Term Exposure Limits

S* - Skin notation

TSCA - Toxic Substance Control Act

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of the safety data sheet