



## SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

SDS # : 083765

### CYLAN WG 680

Date of the previous version: not applicable

Revision Date: 2015-05-14

Version 1

#### 1. IDENTIFICATION

##### Product identifier

Product name CYLAN WG 680

##### Other means of identification

Product Code(s) 083765

Number 7NL  
Substance/mixture Mixture

##### Recommended use of the chemical and restrictions on use

Identified uses Gear oil.

Uses advised against Do not use for any purpose other than the one for which it is intended

##### Details of the supplier of the safety data sheet

Supplier Address TOTAL Specialties USA Inc  
1201 Louisiana Street, Suite 1800  
Houston, TX 77002  
Phone: +1 800 323 3198

Contact Point Technical/ HSEQ

E-mail Address USRMLIN-info@total.com

##### Emergency telephone number

Company Phone Number +1 (908) 862-9300  
Emergency telephone CHEMTREC: +1 800 424 9300 (24h)

#### 2. HAZARDS IDENTIFICATION

##### Classification

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

##### Label elements

This chemical is not considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)



SDS # : 083765

## CYLAN WG 680

Date of the previous version: not applicable

Revision Date: 2015-05-14

Version 1

### Unknown Acute Toxicity

No information available

### Hazards not otherwise classified (HNOC)

- None known

### Other information

- Contaminated surfaces will be extremely slippery
- Should not be released into the environment

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

This material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

## 4. FIRST AID MEASURES

### First aid measures for different exposure routes

|                       |  |
|-----------------------|--|
| <b>General advice</b> | IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.  |
| <b>Eye contact</b>    | Rinse immediately with plenty of water and seek medical advice.  |
| <b>Skin contact</b>   | Remove contaminated clothing and shoes. Wash off with soap and water. Wash contaminated clothing before reuse.                 |
| <b>Inhalation</b>     | Move to fresh air. Inhalation of high concentrations of vapor or aerosols may cause irritation of the upper respiratory tract. |
| <b>Ingestion</b>      | If swallowed, do not induce vomiting - seek medical advice.  |

### Most important symptoms/effects, acute and delayed

|                     |  |
|---------------------|--|
| <b>Skin contact</b> | Not classified.  |
| <b>Eye contact</b>  | Not classified. May cause eye irritation with susceptible persons.                                     |
| <b>Inhalation</b>   | Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system. |
| <b>Ingestion</b>    | Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.        |
| <b>Symptoms</b>     | Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.                   |



SDS # : 083765

## CYLAN WG 680

Date of the previous version: not applicable

Revision Date: 2015-05-14

Version 1

### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** Treat symptomatically.

### **5. FIRE-FIGHTING MEASURES**

**Suitable Extinguishing Media** Foam. Carbon dioxide (CO<sub>2</sub>). ABC powder. Water spray.

**Unsuitable Extinguishing Media** Do not use a solid water stream as it may scatter and spread fire.

**Special Hazard** Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration.

#### **Explosion Data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

**Protective Equipment and Precautions for Firefighters** As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Evacuate non-essential personnel.

### **6. ACCIDENTAL RELEASE MEASURES**

#### **Personal precautions, protective equipment and emergency procedures**

**General Information** Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

**Other information** See Section 12 for additional information.

#### **Environmental precautions**

**General Information** Do not allow material to contaminate ground water system. Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained.

#### **Methods and materials for containment and cleaning up**

**Methods for cleaning up** Dam up. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

### **7. HANDLING AND STORAGE**

#### **Precautions for safe handling**

**Advice on safe handling** When using, do not eat, drink or smoke. For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing.



SDS # : 083765

## CYLAN WG 680

Date of the previous version: not applicable

Revision Date: 2015-05-14

Version 1

|  |  |
|--|--|
| <b>Prevention of fire and explosion</b>                                    | Take precautionary measures against static discharges. Ground/bond containers, tanks and transfer/receiving equipment.   |
| <b>Hygiene measures</b>  | Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.   |
| <b><u>Conditions for safe storage, including any incompatibilities</u></b> |  |
| <b>Technical measures/Storage conditions</b>                               | Keep away from food, drink and animal feedingstuffs. Keep in a banded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Protect from frost, heat and sunlight. Protect from moisture. Design equipment to avoid accidental product leakage (for example due to seal failure) onto hot casings or electrical contacts. |
| <b>Materials to Avoid</b>  | Strong oxidizing agents.   |

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

|                        |  |
|------------------------|--|
| <b>Exposure limits</b> | Mineral oil mist:<br>USA: OSHA (PEL) TWA 5 mg/m <sup>3</sup> , NIOSH (REL) TWA 5 mg/m <sup>3</sup> , STEL 10 mg/m <sup>3</sup> , ACGIH (TLV) TWA 5 mg/m <sup>3</sup> (highly refined). |
|------------------------|--|

#### Exposure controls

|                             |   |
|-----------------------------|---|
| <b>Engineering Measures</b> | Apply technical measures to comply with the occupational exposure limits. |
|-----------------------------|---|

#### **Individual protection measures, such as personal protective equipment**

|                                 |   |
|---------------------------------|---|
| <b>General Information</b>      | If the product is used in mixtures, it is recommended that you contact the appropriate protective equipment suppliers. These recommendations apply to the product as supplied.  |
| <b>Eye/Face Protection</b>      | If splashes are likely to occur, wear: Safety glasses with side-shields.  |
| <b>Skin and body protection</b> | Wear suitable protective clothing. Protective shoes or boots.   |
| <b>Hand Protection</b>          | Protective gloves. Nitrile rubber. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. |



SDS # : 083765

**CYLAN WG 680**

Date of the previous version: not applicable

Revision Date: 2015-05-14

Version 1

**Respiratory protection**

None required under normal usage. If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

**Hygiene measures**

Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Physical and chemical properties**

**Color** amber  
**Physical State @20°C** liquid  
**Odor** Petroleum distillates  
**Odor Threshold** No information available

| <u>Property</u>                           | <u>Values</u>           | <u>Remarks</u>           | <u>Method</u>  |
|---|-------------------------|--------------------------|--|
| <b>pH</b>                                 |                         | Not applicable           |  |
| <b>Melting point/range</b>                |                         | No information available |  |
| <b>Boiling point/boiling range</b>        |                         | Not applicable           |  |
| <b>Flash point</b>                        | <b>299 °C</b><br>570 °F |                          | Cleveland Open Cup (COC)<br>ASTM D 97<br>Cleveland Open Cup (COC).<br>ASTM D 97. |
| <b>Evaporation rate</b>                   | < 1.0                   | @ 25 °C                  |  |
| <b>Flammability Limits in Air</b>         |                         | No information available |  |
| <b>upper</b>                              | -                       | No information available |  |
| <b>Lower</b>                              | -                       | No information available |  |
| <b>Vapor Pressure</b>                     |                         | No information available |  |
| <b>Vapor density</b>                      | > 8                     | (Air = 1)                |  |
| <b>Relative density</b>                   | 0.895                   | @ 15 °C                  | ASTM D 1298  |
| <b>Density</b>                            | 895 kg/m <sup>3</sup>   | @ 15 °C                  | ASTM D 1298  |
| <b>Water solubility</b>                   |                         | Not applicable           |  |
| <b>Solubility in other solvents</b>       |                         | No information available |  |
| <b>logPow</b>                             |                         | No information available |  |
| <b>Autoignition temperature</b>           |                         | No information available |  |
| <b>Decomposition temperature</b>          |                         | No information available |  |
| <b>Viscosity, kinematic</b>               | 620 mm <sup>2</sup> /s  | @ 40 °C                  | ASTM D 445   |
| <b>Explosive properties</b>               | Not explosive           |                          |  |
| <b>Oxidizing Properties</b>               | Not applicable          |                          |  |
| <b>Possibility of hazardous reactions</b> | Not applicable          |                          |  |



SDS # : 083765

**CYLAN WG 680**

Date of the previous version: not applicable

Revision Date: 2015-05-14

Version 1

**Other information**

|                  |       |                          |             |
|------------------|-------|--------------------------|-------------|
| Specific Gravity | 0.895 | @ 15 °C                  | ASTM D 1298 |
| Freezing Point   |       | No information available |             |
| Pour point       | -7 °C |                          | ASTM D 97   |

**10. STABILITY AND REACTIVITY**

|   |  |
|---|--|
| <b>Reactivity</b>                         | No information available.  |
| <b>Chemical stability</b>                 | Stable under recommended storage conditions.   |
| <b>Possibility of hazardous reactions</b> | None under normal processing.  |
| <b>Conditions to Avoid</b>                | Heat, flames and sparks. Take precautionary measures against static discharges. Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Strong oxidizing agents. |
| <b>Incompatible Materials</b>             | Strong oxidizing agents.   |
| <b>Hazardous Decomposition Products</b>   | Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot.                                       |

**11. TOXICOLOGICAL INFORMATION****Acute toxicity****Information on likely routes of exposure****Product Information**

|                     |  |
|---------------------|--|
| <b>Skin contact</b> | Not classified.  |
| <b>Eye contact</b>  | Not classified. May cause eye irritation with susceptible persons.                                     |
| <b>Inhalation</b>   | Not classified. Inhalation of vapors in high concentration may cause irritation of respiratory system. |
| <b>Ingestion</b>    | Not classified. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.        |

**Numerical measures of toxicity - Product Information**

|                               |            |
|-------------------------------|------------|
| ATEmix (oral)                 | 5057 mg/kg |
| ATEmix (dermal)               | 5057 mg/kg |
| <b>Inhalation</b>             |            |
| ATEmix (inhalation-dust/mist) | 5.2 mg/l   |
| ATEmix (inhalation-vapor)     | 30.3 mg/l  |



SDS # : 083765

**CYLAN WG 680**

Date of the previous version: not applicable

Revision Date: 2015-05-14

Version 1

**Information on toxicological effects**

**Symptoms** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** Not classified as a sensitizer.  
**Carcinogenicity** This product is not classified carcinogenic.

**Mutagenicity** Contains no ingredient listed as a mutagen.  
**Reproductive toxicity** This product does not present any known or suspected reproductive hazards.  
**Other adverse effects** Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing).  
**Aspiration Hazard** Not classified.

**12. ECOLOGICAL INFORMATION****Ecotoxicity****Acute aquatic toxicity - Product Information**

No experimental data available

**Acute aquatic toxicity - Component Information**

No information available

**Chronic aquatic toxicity - Product Information**

No experimental data available

**Chronic aquatic toxicity - Component Information**

No information available

**Effects on terrestrial organisms** No experimental data available .

**Persistence and degradability**

**General Information** No information available.

**Bioaccumulative potential**

**Product Information** No information available.



SDS # : 083765

**CYLAN WG 680**

Date of the previous version: not applicable

Revision Date: 2015-05-14

Version 1

logPow No information available

Component Information No information available.

**Mobility**

Soil No information available

**Other adverse effects**

General Information No information available

**13. DISPOSAL CONSIDERATIONS****Waste treatment**

Waste Disposal Methods Dispose of in accordance with local regulations.

Contaminated packaging Dispose of in accordance with local regulations.

**14. TRANSPORT INFORMATION**DOT Not regulatedTDG Not regulatedMEX Not regulatedICAO/IATA Not regulatedIMDG/IMO Not regulatedADR/RID Not regulatedADN Not regulated**15. REGULATORY INFORMATION**

**International Inventories** All the substances contained in this product are listed or exempted from listing in the following inventories:  
U.S.A. (TSCA)

**U.S. Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

**SARA 311/312 Hazard Categories**





SDS # : 083765

**CYLAN WG 680**

Date of the previous version: not applicable

Revision Date: 2015-05-14

Version 1

|                                   |    |
|-----------------------------------|----|
| Acute Health Hazard               | no |
| Chronic Health Hazard             | no |
| Fire Hazard                       | no |
| Sudden Release of Pressure Hazard | no |
| Reactive Hazard                   | no |

**Clean Water Act**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

**Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)**

This product does not contain any substances regulated as hazardous air pollutants (HAPS) under Section 112 of the Clean Air Act Amendments of 1990.

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

**U.S. State Regulations****California Proposition 65**

This product does not contain any Proposition 65 chemicals.

**U.S. State Right-to-Know Regulations**

No information available

**16. OTHER INFORMATION**

|             |                 |                |                   |                                 |
|-------------|-----------------|----------------|-------------------|---------------------------------|
| <b>NFPA</b> | Health Hazard 0 | Flammability 1 | Instability 0     | Physical and chemical hazards - |
| <b>HMIS</b> | Health Hazard 0 | Flammability 1 | Physical Hazard 0 | Personal protection X           |

NFPA (National Fire Protection Association)

HMIS (Hazardous Material Information System)

Hazards are split into categories each with a 0 to 4 rating, 0 meaning no hazard and 4 meaning high hazard

Revision Date: 2015-05-14

Revision Note: No information available

Abbreviations, acronyms



---

SDS # : 083765

## CYLAN WG 680

Date of the previous version: not applicable

Revision Date: 2015-05-14

Version 1

---

### Legend

Section 8  
ACGIH - American Conference of Governmental Industrial Hygienists  
OSHA - Occupational Safety and Health Administration  
NIOSH - National Institute for Occupational Safety and Health  
TLV - Threshold Limit Values  
PEL - Permissible Exposure Limits  
IDHL - Immediately Dangerous to Life or Health concentrations  
TWA - Time Weight Average  
STEL - Short Term Exposure Limits  
S\* - Skin notation  
TSCA - Toxic Substance Control Act

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of the safety data sheet